

# Package: tidyCDISC (via r-universe)

October 12, 2024

**Title** Quick Table Generation & Exploratory Analyses on ADaM-Ish Datasets

**Version** 0.2.1

**Description** Provides users a quick exploratory dive into common visualizations without writing a single line of code given the users data follows the Analysis Data Model (ADaM) standards put forth by the Clinical Data Interchange Standards Consortium (CDISC) <<https://www.cdisc.org>>. Prominent modules/ features of the application are the Table Generator, Population Explorer, and the Individual Explorer. The Table Generator allows users to drag and drop variables and desired statistics (frequencies, means, ANOVA, t-test, and other summary statistics) into bins that automatically create stunning tables with validated information. The Population Explorer offers various plots to visualize general trends in the population from various vantage points. Plot modules currently include scatter plot, spaghetti plot, box plot, histogram, means plot, and bar plot. Each plot type allows the user to plot uploaded variables against one another, and dissect the population by filtering out certain subjects. Last, the Individual Explorer establishes a cohesive patient narrative, allowing the user to interact with patient metrics (params) by visit or plotting important patient events on a timeline. All modules allow for concise filtering & downloading bulk outputs into html or pdf formats to save for later.

**License** AGPL (>= 3)

**URL** <https://github.com/Biogen-Inc/tidyCDISC/>,  
<https://Biogen-Inc.github.io/tidyCDISC/>

**BugReports** <https://github.com/Biogen-Inc/tidyCDISC/issues>

**Depends** R (>= 2.10)

**Imports** cicerone, config, dplyr, DT, GGally, ggcorrplot, ggplot2, glue, golem, gt, haven, IDEAFilter, plotly, purrr, rlang, rmarkdown, shiny, shinyjs, shinyWidgets, sjlabelled, stringr, survival, tidyr, timevis, tippy (== 0.1.0)

**Suggests** knitr, spelling, testthat  
**VignetteBuilder** knitr  
**Encoding** UTF-8  
**Language** en-US  
**LazyData** true  
**RoxygenNote** 7.2.3  
**Repository** <https://biogen-inc.r-universe.dev>  
**RemoteUrl** <https://github.com/biogen-inc/tidycdisc>  
**RemoteRef** HEAD  
**RemoteSha** f41ed77e1fd0df86ad95ec75dbb01efa565d00af

## Contents

adae . . . . .	3
adlbc . . . . .	3
adsl . . . . .	4
adtte . . . . .	4
advs . . . . .	5
app_methods . . . . .	5
col_for_list_expr . . . . .	6
common_rownames . . . . .	7
data_to_filter . . . . .	8
data_to_use_str . . . . .	8
example_dat1 . . . . .	9
example_dat2 . . . . .	10
get_levels . . . . .	10
prep_adae . . . . .	11
prep_adsl . . . . .	12
prep_bds . . . . .	12
pretty_IDs . . . . .	13
run_app . . . . .	14
std_footnote . . . . .	14
tg_gt . . . . .	15
varN_fctr_reorder . . . . .	15

<b>Index</b>	<b>17</b>
--------------	-----------

---

adae	<i>ADAE</i>
------	-------------

---

**Description**

Adverse Events Analysis Data from PHUSE Test Data Factory Project's GitHub.

**Usage**

adae

**Format**

Data frame with 32,139 features and 34 fields

**Source**

<[https://github.com/phuse-org/TestDataFactory/blob/master/Updated/TDF\\_ADaM/adae.xpt](https://github.com/phuse-org/TestDataFactory/blob/master/Updated/TDF_ADaM/adae.xpt)>, downloaded 2020-06-17

---

adlbc	<i>ADLBC</i>
-------	--------------

---

**Description**

Laboratory Results Chemistry Analysis Data from PHUSE Test Data Factory Project's GitHub.

**Usage**

adlbc

**Format**

Data frame with 32,740 features and 58 fields

**Source**

<[https://github.com/phuse-org/TestDataFactory/blob/master/Updated/TDF\\_ADaM/adlbc.xpt](https://github.com/phuse-org/TestDataFactory/blob/master/Updated/TDF_ADaM/adlbc.xpt)>, downloaded 2020-06-17

---

adsl

*ADSL*

---

**Description**

Subject Level Analysis Data from PHUSE Test Data Factory Project's GitHub.

**Usage**

adsl

**Format**

Data frame with 254 features and 51 fields

**Source**

<[https://github.com/phuse-org/TestDataFactory/blob/master/Updated/TDF\\_ADaM/adsl.xpt](https://github.com/phuse-org/TestDataFactory/blob/master/Updated/TDF_ADaM/adsl.xpt)>, downloaded 2020-06-17

---

adtte

*ADTTE*

---

**Description**

Time to Event Analysis Data from PHUSE Test Data Factory Project's GitHub.

**Usage**

adtte

**Format**

Data frame with 32,740 features and 58 fields

**Source**

<[https://github.com/phuse-org/TestDataFactory/blob/master/Updated/TDF\\_ADaM/adtte.xpt](https://github.com/phuse-org/TestDataFactory/blob/master/Updated/TDF_ADaM/adtte.xpt)>, downloaded 2021-01-26

---

advs	<i>ADVS</i>
------	-------------

---

**Description**

Vital Signs Analysis Data from PHUSE Test Data Factory Project's GitHub.

**Usage**

advs

**Format**

Data frame with 32,139 features and 34 fields

**Source**

<[https://github.com/phuse-org/TestDataFactory/blob/master/Updated/TDF\\_ADaM/advs.xpt](https://github.com/phuse-org/TestDataFactory/blob/master/Updated/TDF_ADaM/advs.xpt)>, downloaded 2020-06-17

---

app_methods	<i>Find the proper function to apply to each statistical and column block pairing and use the metadata associated with each column block for the function's arguments</i>
-------------	---

---

**Description**

Find the proper function to apply to each statistical and column block pairing and use the metadata associated with each column block for the function's arguments

**Usage**

```
app_methods(agg, column, week, group, data, totals, filter = NA)
```

**Arguments**

agg	the statistic to apply given the block name
column	the column to apply that statistic too, and class of the column dictated by the data frame it came from
week	the week if needed for calculation
group	whether to perform a group_by and if so by which column
data	the dataset to perform all functions on
totals	the totals data frame that contains denominator N's use when calculating column percentages
filter	a string denoting the additional filter to apply to the dataset

**Value**

the table corresponding to the proper function to perform given the supplied column. This is used within a map to apply to all blocks inside the table generator module.

**Examples**

```
if(interactive()){
  data(example_dat1, package = "tidyCDISC")

  # Create non-missing table section
  app_methods("NON_MISSING",
    structure("USUBJID", class = c("character", "ADSL")), NA,
    "TRT01P", example_dat1$AE, example_dat1$totals)

  # Create ANOVA table section
  app_methods("ANOVA",
    structure("TEMP", class = c("character", "BDS")), "Week 2",
    "TRT01P", example_dat1$BDS, example_dat1$totals)

  # Create change table section
  app_methods("CHG",
    structure("WEIGHT", class = c("character", "BDS")), "Week 12",
    "TRT01P", example_dat1$BDS, example_dat1$totals)

  # Create mean table section
  app_methods("MEAN",
    structure("PULSE", class = c("character", "BDS")), "Baseline",
    "TRT01P", example_dat1$BDS, example_dat1$totals)
}
```

---

col\_for\_list\_expr      *GT Column Names*

---

**Description**

The function creates the labels for each column using the total function so the columns are now NAME N= X

**Usage**

```
col_for_list_expr(col_names, col_total)
```

**Arguments**

col\_names      A vector of column names  
 col\_total      A vector of column totals

**Value**

A character object of class `from_markdown`.

**Examples**

```
data(example_dat2, package = "tidyCDISC")

labels <- col_for_list_expr(example_dat2$col_names, example_dat2$col_totals)
labels

if (interactive()) {
# TG table without nice column labels or totals
example_dat2$TG_table

# TG table with nice column labels and totals
gt::cols_label(example_dat2$TG_table, .list = labels)
}
```

---

common_rownames	<i>Identify Names of Columns</i>
-----------------	----------------------------------

---

**Description**

A function to transform the gt row names from generics to the column name and the total N of each column

**Usage**

```
common_rownames(data, group)
```

**Arguments**

data	the data to create columns with
group	whether to group the data to calculate Ns

**Value**

A character vector

**Examples**

```
data(adsl, package = "tidyCDISC")

# Values of TRT01P
unique(adsl$TRT01P)

# Common row names based on TRT01P
common_rownames(adsl, "TRT01P")
```

---

data\_to\_filter      *The smallest possible data set we could filter to semi-join later*

---

### Description

The smallest possible data set we could filter to semi-join later

### Usage

```
data_to_filter(datafile, input_filter_df)
```

### Arguments

datafile            list of ADaM-ish dataframes  
input\_filter\_df      The name of a dataset stored in 'datafile'

### Value

A 'data.frame' object based on the reduction of 'datafile' from 'input\_filter\_df'.

### Examples

```
if(interactive()) {
  datalist <- list(ADSL = tidyCDISC::adsl, ADAE = tidyCDISC::adae,
                 ADVS = tidyCDISC::advS, ADLBC = tidyCDISC::adlbc,
                 ADTTE = tidyCDISC::adtte)

  # Returns combined dataset
  data_to_filter(datalist, c("ADSL", "ADAE"))
}
```

---

data\_to\_use\_str      *Function to clean and combine ADAE dataset with ADSL*

---

### Description

Function to clean and combine ADAE dataset with ADSL

### Usage

```
data_to_use_str(x, ae_data, bds_data)
```

### Arguments

x                    string, naming a data.frame.  
ae\_data              data.frame, of the AE variety  
bds\_data             data.frame, of the BDS variety



**Value**

A 'data.frame' object containing data of the AE variety if 'x == "ADAE"' or one of the BDS variety if not.

**Examples**

```
if(interactive()) {  
  datalist <- list(ADSL = tidyCDISC::adsl, ADVS = tidyCDISC::adv,  
                 ADAE = tidyCDISC::adae, ADLBC = tidyCDISC::adlbc)  
  
  pre_adsl <- prep_adsl(datalist$ADSL, input_recipe = 'NONE')  
  pre_adae <- prep_adae(datalist, pre_adsl$data, 'NONE')  
  ae_data <- pre_adae$data  
  bds_data <- prep_bds(datalist, ADSL = pre_adsl$data)  
  
  all.equal(data_to_use_str("ADAE", ae_data, bds_data), ae_data)  
  all.equal(data_to_use_str("ADSL", ae_data, bds_data), bds_data)  
}
```

---

example\_dat1

*Example Data Set 1*

---

**Description**

Pre-processed data for purposes of demonstrating [app\\_methods](#).

**Usage**

```
example_dat1
```

**Format**

A list with 3 elements:

**AE** data frame, pre-processed AE dataset

**BDS** data frame, pre-processed BDS dataset

**totals** data frame, contains totals by grouping variable for pre-processed data

---

`example_dat2`*Example Data Set 2*

---

**Description**

Pre-processed data for the purposes of demonstrating [col\\_for\\_list\\_expr](#).

**Usage**

```
example_dat2
```

**Format**

A list with 3 elements:

**TG\_table** data frame, pre-processed gt table object with basic column names

**col\_names** vector, the column names

**col\_totals** vector, totals corresponding to each column

---

`get_levels`*Get Factor Levels*

---

**Description**

Extracts the factor levels of a vector or returns the unique values if the vector is not a factor.

**Usage**

```
get_levels(x)
```

**Arguments**

`x` a vector

**Value**

`x` vector

**References**

A character vector containing the levels of the factor/vector

**Examples**

```

data(adae, package = "tidyCDISC")

# Create levels based on VARN
varN_fctr_adae <- varN_fctr_reorder(adae)

# `adae` does not have factor but `varN_fctr_adae` does
levels(adae$RACE)
levels(varN_fctr_adae$RACE)

# `get_levels()` either creates the factor or retrieves it
get_levels(adae$RACE)
get_levels(varN_fctr_adae$RACE)

```

---

prep\_adae

---

*Function to pre-filter the ADAE depending on the stan table selected*


---

**Description**

Function to pre-filter the ADAE depending on the stan table selected

**Usage**

```
prep_adae(datafile, ADSL, input_recipe)
```

**Arguments**

datafile	list of ADaM-ish dataframes
ADSL	an ADSL data.frame
input_recipe	The shiny input that keeps track of the recipe selected

**Value**

A 'list' containing a 'data.frame' object and character vector specifying the pre-filter applied.

**Examples**

```

if(interactive()) {
  datalist <- list(ADSL = tidyCDISC::adsl, ADVS = tidyCDISC::adv,
                 ADAE = tidyCDISC::adae, ADLBC = tidyCDISC::adlbc)

  pre_adsl <- prep_adsl(datalist$ADSL, input_recipe = 'NONE')

  # Create AE data set
  prep_adae(datalist, pre_adsl$data, input_recipe = 'NONE')
}

```

---

```
prep_adsl          Function to pre-filter the ADSL depending on the stan table selected
```

---

**Description**

Function to pre-filter the ADSL depending on the stan table selected

**Usage**

```
prep_adsl(ADSL, input_recipe)
```

**Arguments**

```
ADSL          an ADSL data.frame
input_recipe  The shiny input that keeps track of the recipe selected
```

**Value**

A ‘list‘ containing a ‘data.frame‘ object and character vector specifying the pre-filter applied.

**Examples**

```
data(adsl, package = "tidyCDISC")

# Process ADSL data for STAN table
prep_adsl(adsl, input_recipe = 'Table 3: Accounting of Subjects')

# Return ADSL data if no STAN table selected
prep_adsl(adsl, input_recipe = "NONE")
```

---

```
prep_bds          Combine BDS Data Frames
```

---

**Description**

A function to combine all BDS data frames into one large data set.

**Usage**

```
prep_bds(datafile, ADSL)
```

**Arguments**

```
datafile      list of ADaM-ish data frames
ADSL          A data frame which contains the ADSL data
```

**Value**

A data frame containing the BDS data bound by rows.

**Examples**

```
if(interactive()) {
  datalist <- list(ADSL = tidyCDISC::adsl, ADVS = tidyCDISC::adv,
                 ADAE = tidyCDISC::adae, ADLBC = tidyCDISC::adlbc)

  pre_adsl <- prep_adsl(datalist$ADSL, input_recipe = 'NONE')

  prep_bds(datalist, ADSL = pre_adsl$data)
}
```

---

pretty\_IDs

*Create Pretty IDs for TG Table*

---

**Description**

Replaces ugly ID patterns of a stat block with pretty replacements for display purposes (e.g. NON\_MISSING becomes Subject Count for those with Non Missing values)

**Usage**

```
pretty_IDs(ID)
```

**Arguments**

ID                      The ID vector of a TG table

**Value**

A character vector of pretty IDs.

**Examples**

```
# List of patterns that can be replaced
patterns <- c("MEAN", "FREQ", "CHG", "Y_FREQ", "MAX_FREQ", "NON_MISSING",
             "NESTED_FREQ_DSC", "NESTED_FREQ_ABC")
IDs <- paste(patterns, "of VAR")

IDs
pretty_IDs(IDs)
```

---

run_app	<i>Run the Shiny Application</i>
---------	----------------------------------

---

**Description**

Run the Shiny Application

**Usage**

```
run_app(...)
```

**Arguments**

... A series of options to be used inside the app.

**Value**

No return value, called to run the application.

---

std_footnote	<i>Create Standard Footnotes for TG Table</i>
--------------	---

---

**Description**

Creates a footnote with a source on the left and date run on the right.

**Usage**

```
std_footnote(data, source)
```

**Arguments**

data	The 'gt' table object to append the footnote
source	The source of the data in the table

**Value**

a 'gt' object

---

tg_gt	<i>Prepare the table generator data for output</i>
-------	--

---

**Description**

Prepare the data.frame so that it's ready for output via 'gt' or other

**Usage**

```
tg_gt(tg_datalist, blockData, total_df, group)
```

**Arguments**

tg_datalist	A list containing the data frames used to create the table
blockData	The data for the construction of the blocks in the table
total_df	A data frame containing the totals by grouping variable
group	A character denoting the grouping variable

**Value**

a data.frame containing output polished for presentation in 'gt'

---

varN_fctr_reorder	<i>Re-order Factor Levels by VARN</i>
-------------------	---------------------------------------

---

**Description**

Function to that looks for VARN counterparts to any character or factor VAR variables in any dataframe and re-orders there factor levels, taking the lead from VARN's numeric guide.

**Usage**

```
varN_fctr_reorder(data)
```

**Arguments**

data	a dataframe, including one enriched with SAS labels attributes
------	--

**Value**

The data frame after having factor levels re-ordered by VARN

**Examples**

```
data(adae, package = "tidyCDISC")

varN_fctr_adae <- varN_fctr_reorder(adae)

unique(adae[,c("AGEGR1", "AGEGR1N")])
levels(adae$AGEGR1)
levels(varN_fctr_adae$AGEGR1)

unique(adae[,c("RACE", "RACEN")])
levels(adae$RACE)
levels(varN_fctr_adae$RACE)
```



# Index

- \* **datasets**
  - adae, 3
  - adlbc, 3
  - adsl, 4
  - adtte, 4
  - adv, 5
  - example\_dat1, 9
  - example\_dat2, 10
- \* **helpers**
  - get\_levels, 10
  - varN\_fctr\_reorder, 15
- \* **tabGen\_repro**
  - app\_methods, 5
  - col\_for\_list\_expr, 6
  - common\_rownames, 7
  - data\_to\_filter, 8
  - data\_to\_use\_str, 8
  - prep\_adae, 11
  - prep\_adsl, 12
  - prep\_bds, 12
  - pretty\_IDs, 13
  - std\_footnote, 14
  - tg\_gt, 15
- \* **tableGen Functions**
  - app\_methods, 5

adae, 3

adlbc, 3

adsl, 4

adtte, 4

adv, 5

app\_methods, 5, 9

col\_for\_list\_expr, 6, 10

common\_rownames, 7

data\_to\_filter, 8

data\_to\_use\_str, 8

example\_dat1, 9

example\_dat2, 10

get\_levels, 10

prep\_adae, 11

prep\_adsl, 12

prep\_bds, 12

pretty\_IDs, 13

run\_app, 14

std\_footnote, 14

tg\_gt, 15

varN\_fctr\_reorder, 15